

## **Product information**

December 2013

# **Banner Cota 510**

510 g/m<sup>2</sup>

### **Material Description**

Flexible matt white banner material for in and outside frontlit banner applications. Banner Cota offers exceptional outdoor durability. Banner Cota is applicable for billboard, banners, building murals and in store displays. B1 Fire retardant!.

#### Qualifications

- Density: 1000x1000 / 20x20
- Soft and delicate surface
- Print side: matt white surface
- Available in 1100, 1370,1600, 2640 &
  - 3200mm

- UV protected
- Seamable

**Details** 

Suitable for in and outdoor banners, printed with UV, (eco) solvent & Latex inks. Packed in strong carton tubes and rolls are wrapped and protected inside the tube.

## **Applications**

- In and outdoor flexible signs and banners.
- Exhibitions
- Events
- Banners trade show.

### **Physical Properties**

Quality		PVC
Weight		510 g/m²
Thickness		0,43mm
Print side		White Matt surface
Reverse side		Matt
Fire retardent		B1 - Quick mix cerificate
Density / yarn		1000x1000 / 20x20
Tearing strenght	N/5cm	240
Tensile strenght	N/5cm	2400
Polyvinylchloride (PVC)		75 - 80%

## Compatibility

Printable with HP LATEX, MIMAKI, ROLAND, MUTOH, SEIKO, ETC... UV CurableSolventEco SolventLatex

Make your own practical test to be sure it reaches your quality standard.

For all- and latest information see our Compatibility List.

Printing guidelines

Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

**Colour profiles** 

ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

Storage conditions

1 year under normal conditions Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place. Storage condition: temperature 10-25° / relative humidity 50%

**Environment** 

The media and final prints can be disposed as PVC. Material is suitable for recycling. Please consult local recycle resources.

Data presented in this product information serve only as a guide-line for compatibility and use. ATgraphix will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice. ATgraphix, The Netherlands. www.atgraphix.com