

# Display PP blackout film SB

**205µm**

**Material Description** High quality polypropylene blackout display film with a nice smooth finish. This PP is tear resistant, and has a proper light transmission for exact colour expression. Polypropylene is an more environmentally responsible product. Polypropylene contain only carbon and hydrogen atoms, it does not poison environment after its disposal heavily.

- Qualifications**
- PP base material
  - High opacity blackout film
  - Print side: Matt surface
  - Reverse side: Grey back
  - Available in 36+, 42+x 30m
  - Core size: 3+

- Details**
- Suitable printing condition: temperature 15-30°C / humidity 30-60%
  - Compatible with eco, mild ,heavy solvent, UVC compatible.
  - Use care in handling printed material, surface susceptible to abrasion
  - Ambient temperature and weather can affect the condition of the product

- Applications**
- Presentation systems (roll ups...)
  - Trade show applications
  - High resolution graphics
  - Shop displays
  - POS

**Physical Properties**

Quality		PET & PP
Weight		160g/m <sup>2</sup>
Thickness		205 µm test method: ASTM D645
Print side		Matt finish
Reverse side		Silver Blockout backing
L.a.b.		90/0 /-5 test method: ANSI T (D50/2°/Abs/No)
glossiness		60°:15,0/85°:30,0 test method: ASTM 2457

- Compatibility**
- Nur**  
**Vutek**  
**Hewlett Packard**  
**Roland**  
**Mimaki**  
**Mutoh**  
**And more...**
-  Solvent
  -  Mild solvent
  -  Eco solvent
  -  UV Curable

Make your own practical test to be sure it reaches your quality standard.  
 For all- and latest information see our Compatibility List.

**Printing guidelines** Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

**Colour profiles** ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

**Storage conditions** 1 year under normal conditions (10. 25°C at a relative humidity of 50 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

**Environment** The media and final prints can be disposed as Polypropylene . Material is suitable for recycling. Please consult local recycle resources.