

WALLPAPER PB – 300gsm

Material Description

Matt Vinyl wall covering on paper base, suitable for (eco) solvent, Latex and UV curable inkjet printing. Specially formulated acrylic lacquer with exclusive inkjet receiver layer. Wallpaper and image can be protected by clear acrylic overcoat by machine or roller. Available in 5 different finishes...

Qualifications

- Light fastness 7 to 8 woolscale
- UV-protected*
- Easy to clean with mild soap
- Resistant to mould bacteria and fungi
- Bio Pruf on request
- Imo quality (Lloyd's)
- Euro Class Fire retardent.

Washability / Resistant

In general: Digitally printed wall covering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent And a damp cloth. Dabbing—certainly not rubbing is recommended to lift the soil. Bleach, abrasive cleaners and similar compounds must not be used.






- Resistant to: Soap, Detergents, Alcohol, Ammonia, Alkali, Diluted acids
- Not resistant to: Solvents like ketones, Esters, Aromatic hydrocarbos

Applications

- Wall covering
- Exhibitions
- Events
- Prolonged presentations

Compatibility

Nur, Vutek, Hewlett Packard, Roland, Mimaki, Mutoh, And more....

-  Eco Solvent
-  Solvent
-  Latex
-  UV-curable
-  UV-curable Led

Printing guidelines

Max. temperature (material) should not exceed 80°C as overheating can impair the flatness of the media. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Storage conditions

1 year under normal conditions (10–25°C at a relative humidity of 30–75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

