

Mesh Durastrip

360 g/m²

Material Description White knitted substrate for small and wide format front-lit display. Mesh with fabric backing, Easy printing without leaking ink, Simply tear-off backing after printing. Building murals & wraps, indoor wall decoration, banners, trade show and in-store display. Weather resistant

- Qualifications**
- Polyvinylchloride (PVC) Mesh
 - Thin PVC Liner
 - Print side: matt white surface
 - Reverse side: White matt surface
 - Available in 1100, 1250, 1372, 1600, 2200, 2.500 & 3200mm x 50m





- Details**
- Ambient temperature and weather can affect the condition of the product.

- Applications**
- Building murals & wraps
 - Indoor wall decoration
 - Banners trade show
 - In-store display

Physical Properties

Quality		PVC
Weight		360 g/m ²
Thickness		0,45mm
Print side		White Matt surface
Reverse side		White Matt
Liner		PVC
Polyvinylchloride (PVC)		75-80%
Ca, Zn Stabilizer		1-5%
Epoxidized Soybean oil		1-5%
Polyester		25-30%
Pe paraffin		0.01-0.1%
Stearate		0.01-0.1%

Compatibility Printable with LATEX, VUTEK, SCITEX, NUR, DGI, MIMAKI, ROLAND, MUTOH, SEIKO, JET-I, ETC...

-  UV Curable
-  Solvent
-  Eco Solvent
-  Latex

Make your own practical test to be sure it reaches your quality standard. For all- and latest information see our Compatibility List.

Printing guidelines Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles ATgraphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists who can produce your profile if it's not direct available from our library. Please contact us for the possibilities.

Storage conditions 1 year under normal conditions Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place. Storage condition: temperature 10-25° / relative humidity 50%

Environment The media and final prints can be disposed as PVC. Material is suitable for recycling. Please consult local recycle resources.